

Display your vision

**MOTOMETER**

# USB Charger

## Our MOTOMETER USB Charger

With its two USB 2.0 ports, our Charger allows for the simultaneous charging of two devices, while the LED backlighting ensures optimal use in the darkness. Thanks to its standard size, the USB Charger can be easily integrated into a rocker-switch panel. The protective cap shields the ports from water and dirt, while the design is engineered for operating voltages of 12 and 24 volts.

Discover the future of vehicle charging technology with MOTOMETER and experience comfort and reliability on every journey. If you have any questions or need personal assistance, we are here to help – contact us today!

[Contact us now](#)



## USB Charger data:

### Technical details:

Supply voltage:	8 - 28 V
Nominal voltage:	12 V / 24 V
Temperature range:	-40 °C up to + 60°C
Single port output current:	2,4A DC
Max output current: (using both ports)	3,1A DC

Drawing: [Watch product drawing](#)

**Part No.** 731 001 1011

### Housing

Mounting dimensions:	21,2 x 37,2 mm or 29,2 mm Ø
Dimensions:	24,5 x 48,5 mm
Protection class:	front: IP 65 (closed cap) rear: IP 65

## Spezielle Wünsche? Wir liefern kundenspezifische Lösungen!

Neben den aufgeführten standardmäßigen Temperaturregler können wir Ihnen gerne kundenspezifische Lösungen anbieten. Kontaktieren Sie uns dazu ganz einfach mit Ihren Anforderungen über den nebenstehenden Button: