

# Intelligent Cockpit Switch

## **MOTOMETER**

### **Our MOTOMETER Intelligent Cockpit Switch**

Our cockpit switch offers a variety of programmable functions and can be universally used in different vehicles. From intelligent sensor signal detection to monitoring external loads and electrical consumers, our switch optimizes efficiency and minimizes standby power consumption, even when the vehicle is turned off. With its compact standard size of 42 x 22 mm, our cockpit switch easily replaces conventional push buttons and can be directly connected to the existing wiring harness.

Personalize the design and color of the robust membrane keypad according to your preferences. Discover the future of cockpit management with MOTOMETER!

For further information or to order your intelligent cockpit switch, feel free to contact us today. Our team is available for individual consultation and support to ensure that you receive the appropriate solution for your needs: [Contact us now](#)



### **The technical specifications of our Intelligent Cockpit Switch:**

#### **Features**

- Intelligent recording, monitoring, evaluation and switching of electronic signals
- Programmable
- Customized design and color of keypad and LEDs possible
- Mounting into standard cut-outs ("Rocker"-Switch)
- Status feedback + self-analysis possible
- Optionally with LIN-, CAN- or customer-specific interface

#### **Optional interfaces**

- For example: LIN, CAN, etc.
- Further interfaces on demand

### **Do you have questions or would you like to order our Intelligent Cockpit Switch?**

Contact us now to learn more about the versatile applications of the Intelligent Cockpit Switch, place orders, or receive customized offers. We look forward to assisting you in getting the most out of our product!

# Intelligent Cockpit Switch

## **MOTOMETER**

### **Technical Specifications**

- **Voltage range:** 5.5 – 40 V
- **Under voltage lockout:** 5.5 V
- **Power output:** max. 8 A continuous current
- **Stand-by current:** typ. 15  $\mu$ A
- **Operating current:** typ. 20 mA
- **Input current:** typ. 5 mA
- **Control logic:** programmable
- **Delay time:** programmable
- **Operating temperature:** -30 up to + 85°C
- **Ingress protection:** IP54
- **Housing:** PA66
- **Operating cycles:** min. 500,000
- **Part No.:** 670 003 0003

### **Do you have questions or would you like to order our Intelligent Cockpit Switch?**

Contact us now to learn more about the versatile applications of the Intelligent Cockpit Switch, place orders, or receive customized offers. We look forward to assisting you in getting the most out of our product!