

# USB-A Charger

## MOTOMETER

### Our MOTOMETER USB Charger

With its two USB 2.0 ports, our Charger allows for the simultaneous charging of two devices, while the LED backlighting ensures optimal use in the darkness. Thanks to its standard size, the USB Charger can be easily integrated into a rocker-switch panel. The protective cap shields the ports from water and dirt, while the design is engineered for operating voltages of 12 and 24 volts.

Discover the future of vehicle charging technology with MOTOMETER and experience comfort and reliability on every journey. If you have any questions or need personal assistance, we are here to help – contact us today!

[Contact us now](#)



### USB Charger data:

#### Technical details:

|   |                     |
|---|---------------------|
| Supply voltage:                           | 8 - 28 V            |
| Nominal voltage:                          | 12 V / 24 V         |
| Temperature range:                        | -40 °C up to + 60°C |
| Single port output current:               | 2,4A DC             |
| Max output current:<br>(using both ports) | 3,1A DC             |

Drawing: [Watch product drawing](#)  
**Part No.** 731 001 1011

#### Housing

|                      |  |
|----------------------|--|
| Mounting dimensions: | 21,2 x 37,2 mm<br>or 29,2 mm Ø           |
| Dimensions:          | 24,5 x 48,5 mm                           |
| Protection class:    | front: IP 65<br>(closed cap) rear: IP 65 |

### We offer tailored solutions for your individual product requirements!

Do not hesitate to contact us via our contact form to discuss special requests and customized product adaptations. Our experienced team is always available to understand your requirements and provide you with the optimal solution.