

Magnet Switch

MOTOMETER



Our MOTOMETER Magnet Switch

Our Magnet Switch provides a cost-effective, reliable, and easy-to-install solution for a variety of applications. With an IP67 protection rating, it is suitable for use in demanding environments. Its rated voltage of 48V and current of 0.5A make it versatile for various uses. Even in extreme operating temperatures ranging from -40 to +85°C, it remains reliably functional. Crafted from high-quality materials (PA6 & GF30), it is durable and robust.

Whether you intend to use it in the automotive industry, mechanical engineering, or other fields, our Magnet Switch offers the performance and reliability you need.

Technical specifications

Protection class: IP 67

Nominal Voltage: 48V / Nominal Current: 0,5 A

Operating Temperature: -40 ... +85 °C

Material: PA6 & GF30



Benefits

- Cost-effective
- Reliable
- Simple installation

Special wishes? We deliver customized solutions!

In addition to the standard products listed, we can also offer you customized solutions specific solutions. Contact us now with your requirements!

Our different Magnet Switch variants:

	P74 012 0001	P74 012 0004
Product Image		
Drawing	Drawing	Drawing
Thread	M12x1	M12x1
Thread Length	36 mm	36 mm
Connector	AMP Superseal 2 pol.	AMP Superseal 2 pol.
Nominal Power	20 W	10 W
Feature	N/O	N/O
Shop Link	Discover now	Discover now

Special wishes? We deliver customized solutions!

In addition to the standard products listed, we can also offer you customized solutions specific solutions. Contact us now with your requirements!